

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_PC35-50-4-4/199\_U

Rev.: C



### Description

Straight cable plug for flexible cable

Interface standards  
IEC 60169-23

### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 33 GHz

#### Mechanical Data

Centre contact plugged  
Outer contact crimped  
Weight 0.0079 kg

#### Environmental Data

Operating Temperature -65 °C to 90 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	PS
Coupling nut	Stainless Steel
Gasket	MVQ (Silicone Rubber)
Crimp ferrule	Copper

##### Surface Plating

Gold Plating
Passivated (Plating)
Passivated (Plating)
Passivated (Plating)
SUCOPLATE (R) Plating

#### Related Documents

Outline drawing	DOU-00007590
Assembly instruction	DOC-0000179057

#### Ordering Information

Single package	11_PC35-50-4-4/199_UE
----------------	-----------------------

#### Additional Information

Suitable cables	S_04212_B, S_04272_B
-----------------	----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**