




1/4" Superflexible Foam Dielectric, FSJ Series – 50-ohm



FSJ1-50A

Description	Type No.
Cable Ordering Information	
Standard Superflexible Cable	
1/4" Standard Cable, Standard Jacket	FSJ1-50A
Fire Retardant Cables	
1/4" Fire Retardant Jacket (CATVX)	FSJ1RN-50B
1/4" Fire Retardant Jacket (CATVR)	FSJ1RN-50B
Low VSWR and Specialized Cables	
1/4" Low VSWR, specify operating band	FSJ1P-50A(**)
Phase Stabilized and Phase Measured Cable	See page 590
Jumper Cable Assemblies – See page 584	

** Insert suffix number from "Low VSWR Specifications" table, page 476.

Characteristics

Electrical	
Impedance, ohms	50 ± 1
Maximum Frequency, GHz	20.4
Velocity, percent	84
Peak Power Rating, kW	6.4
dc Resistance, ohms/1000 ft (1000 m)	
Inner	3.0 (9.8)
Outer	2.0 (6.5)
dc Breakdown, volts	1600
Jacket Spark, volts RMS	5000
Capacitance, pF/ft (m)	24.2 (79.4)
Inductance, µH/ft (m)	0.061 (0.200)
Mechanical	
Outer Conductor	Copper
Inner Conductor	Cu-Clad Al
Diameter over Jacket, standard jacket, in (mm)	0.29 (7.4)
Diameter over Jacket, fire-retardant jacket, in (mm)	0.29 (7.4)
Diameter Copper Outer Conductor, in (mm)	0.25 (6.4)
Diameter Inner Conductor, in (mm)	0.075 (1.9)
Minimum Bending Radius, in (mm)	1 (25)
Number of Bends, minimum (typical)	15 (20)
Bending Moment, lb-ft (N•m)	0.8 (1.1)
Cable Weight, lb/ft (kg/m)	0.045 (0.067)
Tensile Strength, lb (kg)	150 (68)
Flat Plate Crush Strength, lb/in (kg/mm)	100 (1.8)

Attenuation and Average Power

Frequency MHz	Attenuation dB/100 ft	Attenuation dB/100 m	Average Power, kW
0.5	0.124	0.407	6.40
1	0.176	0.577	6.40
1.5	0.215	0.707	6.40
2	0.249	0.816	6.40
10	0.559	1.83	3.97
20	0.792	2.60	2.80
30	0.973	3.19	2.28
50	1.26	4.14	1.76
88	1.68	5.52	1.32
100	1.79	5.89	1.23
108	1.87	6.13	1.19
150	2.21	7.25	1.00
174	2.39	7.82	0.929
200	2.56	8.41	0.865
300	3.16	10.4	0.701
400	3.67	12.1	0.603
450	3.91	12.8	0.567
500	4.13	13.5	0.537
512	4.18	13.7	0.530
600	4.54	14.9	0.488
700	4.93	16.2	0.450
800	5.29	17.4	0.419
824	5.38	17.6	0.412
894	5.61	18.4	0.395
960	5.83	19.1	0.380
1000	5.96	19.6	0.372
1250	6.72	22.0	0.330
1500	7.41	24.3	0.299
1700	7.94	26.0	0.279
1800	8.19	26.9	0.271
2000	8.67	28.5	0.256
2100	8.91	29.2	0.249
2200	9.14	30.0	0.243
2300	9.37	30.7	0.237
3000	10.9	35.6	0.204
3400	11.6	38.2	0.191
4000	12.8	41.8	0.174
5000	14.5	47.5	0.153
6000	16.1	52.7	0.138
8000	19.0	62.4	0.117
10000	21.7	71.2	0.102
12000	24.2	79.4	0.092
14000	26.6	87.2	0.084
16000	28.8	94.6	0.077
18000	31.0	101.7	0.072
19000	32.1	105.2	0.069
20000	33.1	108.6	0.067
20400	33.5	110.0	0.066

Standard Conditions:

For Attenuation. VSWR 1.0, ambient temperature 20°C (68°F).

For Average Power. VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 100°C (212°F); no solar loading.