



## 1/4" Foam Dielectric, LDF Series – 50-ohm



### LDF1-50

Description	Type No.
<b>Cable Ordering Information</b>	
<b>Standard Cable</b>	
1/4" Standard Cable, Standard Jacket	<b>LDF1-50</b>
<b>Fire Retardant Cables</b>	
1/4" Fire Retardant Jacket (CATVX)	<b>LDF1RN-50</b>
1/4" Fire Retardant Jacket (CATVR)	<b>LDF1RN-50</b>
<b>Jumper Cable Assemblies</b> – See page 584	

#### Characteristics

<b>Electrical</b>	
Impedance, ohms	50 ± 1
Maximum Frequency, GHz	15.8
Velocity, percent	86
Peak Power Rating, kW	12.1
dc Resistance, ohms/1000 ft (1000 m)	
Inner	1.57 (5.15)
Outer	1.02 (3.33)
dc Breakdown, volts	2200
Jacket Spark, volts RMS	5000
Capacitance, pF/ft (m)	23.4 (76.8)
Inductance, µH/ft (m)	0.059 (0.19)
<b>Mechanical</b>	
Outer Conductor	Copper
Inner Conductor	Copper-Clad Aluminum
Diameter over Jacket, in (mm)	0.345 (8.8)
Diameter over Copper Outer Conductor, in (mm)	0.31 (7.7)
Diameter Inner Conductor, in (mm)	0.102 (2.6)
Minimum Bending Radius, in (mm)	3.0 (76)
Number of Bends, minimum (typical)	15 (30)
Bending Moment, lb-ft (N•m)	0.98 (1.33)
Cable Weight, lb/ft (kg/m)	0.06 (0.09)
Tensile Strength, lb (kg)	200 (91)
Flat Plate Crush Strength, lb/in (kg/mm)	80 (1.4)

#### Attenuation and Average Power Ratings

Frequency MHz	Attenuation dB/100 ft	Attenuation dB/100 m	Average Power, kW
0.5	0.085	0.278	12.1
1	0.120	0.394	12.1
1.5	0.147	0.483	12.1
2	0.170	0.558	12.1
10	0.382	1.25	5.79
20	0.543	1.78	4.08
30	0.667	2.19	3.32
50	0.865	2.84	2.56
88	1.16	3.79	1.92
100	1.23	4.05	1.79
108	1.28	4.21	1.72
150	1.52	4.99	1.45
174	1.64	5.39	1.35
200	1.77	5.80	1.25
300	2.18	7.17	1.01
400	2.54	8.34	0.871
450	2.71	8.88	0.818
500	2.86	9.39	0.773
512	2.90	9.51	0.764
600	3.15	10.4	0.702
700	3.43	11.2	0.646
800	3.68	12.1	0.601
824	3.74	12.3	0.592
894	3.91	12.8	0.566
960	4.07	13.3	0.545
1000	4.16	13.6	0.533
1250	4.70	15.4	0.471
1500	5.19	17.0	0.426
1700	5.57	18.3	0.398
1800	5.75	18.9	0.385
2000	6.10	20.0	0.363
2100	6.27	20.6	0.353
2200	6.43	21.1	0.344
2300	6.60	21.6	0.336
3000	7.67	25.2	0.289
3400	8.24	27.0	0.269
4000	9.06	29.7	0.245
5000	10.3	33.9	0.215
6000	11.5	37.7	0.193
8000	13.7	44.9	0.162
10000	15.7	51.5	0.141
12000	17.6	57.7	0.126
14000	19.4	63.5	0.114
15800	20.9	68.6	0.106

#### Standard Conditions:

For attenuation. VSWR 1.0, ambient temperature 20°C (68°F).

For Average Power, VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 100°C (212°F), no solar loading.